



PURITY ZINC METALS, LLC

290 International Boulevard
 Chattanooga, TN
 37427-0020
 423.552.5400
 fax 423.552.5588
 www.purityzinc.com

UltraPure[®] grades meet ASTM D520 Type III Specification for Zinc Dust Pigment

UP5T with Lime PRODUCT SPECIFICATIONS

| Property | Specification | Typical |
|-------------------------------------|---------------|---------|
| Total Zinc (% minimum) | 99 | 99.2 |
| Metallic Zinc (% minimum) | 95.5 | 96.3 |
| Iron (% maximum) | 0.002 | 0.0003 |
| Lead (% maximum) | 0.002 | 0.0015 |
| Copper (% maximum) | 0.001 | 0.0005 |
| Cadmium (% maximum) | 0.0005 | 0.0001 |
| Lime (Calcium Oxide) | 0.25 - 0.6 | 0.4 |
| Zinc Oxide | Balance | Balance |
| Average Particle Size* | 4.5 - 5.5 | 5.0 |
| Retained on 100 mesh screen (% max) | Nil | Nil |
| Retained on 200 mesh screen (% max) | 0.1 | 0.001 |
| Retained on 325 mesh screen (% max) | 0.3 | 0.04 |
| Specific Gravity | 7.0 - 7.1 | |

* Air Permeability Method

APPLICATIONS

- Coatings: Organic and inorganic
- Reducing agent
- Thread compounds
- Precipitating agent
- Purification Applications
- Zinc Plating

NOTE: All Purity Zinc Metals, LLC UltraPure[®] dusts are produced from 99.995% pure zinc metal. UltraPure[®] grades of zinc dust are manufactured under license from Purity Zinc Metals[™] a Division of North American Zinc Company.

We believe the information herein to be reliable but we assume no responsibility for its accuracy. It will be the users responsibility exclusively to determine the suitability for these grades for the product manufactured by the user.